

View Online at <https://aerobasegroup.com/nsn/5950-00-552-0501>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility single center group3.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single componentinternal shield grounded to inclosure and brought out to terminal single component

Body Length:

4.688 inches 4.688 inches

Body Width:

4.000 inches 4.000 inches

Body Height:

4.938 inches 4.938 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

280.0 milliamperes ac single component single secondary

Winding Operating Voltage:

2.16 ac kilovolts single component single secondary117.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff insulator and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0