

View Online at <https://aerobasegroup.com/nsn/5950-00-552-0513>

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group 2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group 2.125 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single components single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component internal shield grounded to inclosure and brought out to terminal single component

Body Length:

3.562 inches 3.562 inches

Body Width:

3.062 inches 3.062 inches

Body Height:

4.875 inches 4.875 inches

Inclosure Type:

Hermetically sealed hermetically sealed

Mounting Facility Quantity:

4 single group 4 single group

Mounting Method:

Threaded stud single group threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group 32 single group

Thread Size:

0.164 inches single group 0.164 inches single group

Winding Operating Current:

138.0 milliamperes dc single component single secondary

Winding Operating Voltage:

117.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff insulator and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0