

View Online at <https://aerobasegroup.com/nsn/5950-00-552-0891>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group1.875 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group0.188 inches single group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

2.750 inches 2.750 inches

Body Width:

2.625 inches 2.625 inches

Body Height:

3.187 inches 3.187 inches

Inclosure Type:

Partially enclosed, double shellpartially enclosed, double shell

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and slot single groupslot single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Winding Operating Current:

50.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

30.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0