

View Online at <https://aerobasegroup.com/nsn/5950-00-552-0960>

Reliability Indicator:

Not establishednot establishednot established

Overall Length:

3.312 inches 3.312 inches 3.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.359 inches single mounting facility single center group and 2.359 inches single mounting facility single center group and 2.359 inches single mounting facility single center group and 2.391 inches single mounting facility single center group2.391 inches single mounting facility single center group2.391 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.359 inches single mounting facility single center group and 1.359 inches single mounting facility single center group and 1.359 inches single mounting facility single center group and 1.391 inches single mounting facility single center group1.391 inches single mounting facility single center group1.391 inches single mounting facility single center group

Overall Height:

4.406 inches 4.406 inches 4.406 inches

Overall Width:

2.562 inches 2.562 inches 2.562 inches

Frequency Rating:

60.0 hertz single component60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Maximum Transformer Power Rating:

12.0 decibels single component12.0 decibels single component12.0 decibels single component

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component2 secondary single component

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Voltage:

77.00 ac volts single component single primary and 110.00 ac volts single component single primary and 220.00 ac volts single component single primary and 310.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure: