

View Online at <https://aerobasegroup.com/nsn/5950-00-552-1344>

**Reliability Indicator:**

Not establishednot established

**Overall Height:**

2.812 inches 2.812 inches

**Frequency Rating:**

380.0 hertz single component380.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

**Body Length:**

2.656 inches 2.656 inches

**Body Width:**

2.906 inches 2.906 inches

**Body Height:**

2.062 inches 2.062 inches

**Maximum Operating Temp:**

65.0 degrees celsius65.0 degrees celsius

**Distance Between Mounting Facility Centers:**

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

2 single group2 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thready Qty Per Inch (tpi):**

24 single group24 single group

**Thread Size:**

0.190 inches single group0.190 inches single group

**Winding Operating Current:**

3.9 amperes ac single component single secondary

**Winding Operating Voltage:**

120.00 ac volts single component single primary31.00 ac volts single component single secondary and 33.00 ac volts single component single secondary and 35.00 ac volts single component single secondary and 37.00 ac volts single component single secondary and 39.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 standoff, wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0