

View Online at <https://aerobasegroup.com/nsn/5950-00-552-1344>

Reliability Indicator:

Not establishednot established

Overall Height:

2.812 inches 2.812 inches

Frequency Rating:

380.0 hertz single component380.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

2.656 inches 2.656 inches

Body Width:

2.906 inches 2.906 inches

Body Height:

2.062 inches 2.062 inches

Maximum Operating Temp:

65.0 degrees celsius65.0 degrees celsius

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

24 single group24 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

3.9 amperes ac single component single secondary

Winding Operating Voltage:

120.00 ac volts single component single primary31.00 ac volts single component single secondary and 33.00 ac volts single component single secondary and 35.00 ac volts single component single secondary and 37.00 ac volts single component single secondary and 39.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 standoff, wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0