## NSN 5950-00-552-9628

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-552-9628

| Reliability Indicator:   |
|--|
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  |
| 2.625 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:   |
| 2.125 inches single mounting facility single center group  |
| Frequency Rating:  |
| 60.0 hertz single component  |
| Input-output Phase Relationship:   |
| Single phase to single phase single component  |
| Body Length:   |
| 3.562 inches   |
| Body Width:  |
| 3.062 inches   |
| Body Height:   |
| 3.875 inches   |
| Inclosure Type:  |
| Hermetically sealed with oil   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded stud single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 4 secondary single component  |
|  |
| Thready Qty Per Inch (tpi):  |
| Thready Qty Per Inch (tpi): 32 single group  |
|  |
| 32 single group  |
| 32 single group Thread Size:   |
| 32 single group  Thread Size: 0.164 inches single group  |
| 32 single group  Thread Size:  0.164 inches single group  Winding Operating Current:   |
| 32 single group  Thread Size: 0.164 inches single group  Winding Operating Current: 3.0 amperes ac single component 4th secondary  |
| 32 single group  Thread Size:  0.164 inches single group  Winding Operating Current:  3.0 amperes ac single component 4th secondary  Winding Operating Voltage:  |
| 32 single group  Thread Size:  0.164 inches single group  Winding Operating Current:  3.0 amperes ac single component 4th secondary  Winding Operating Voltage:  6.30 ac volts single component all secondary  |
| 32 single group  Thread Size: 0.164 inches single group  Winding Operating Current: 3.0 amperes ac single component 4th secondary  Winding Operating Voltage: 6.30 ac volts single component all secondary  Thread Series Designator:  |
| 32 single group  Thread Size:  0.164 inches single group  Winding Operating Current:  3.0 amperes ac single component 4th secondary  Winding Operating Voltage:  6.30 ac volts single component all secondary  Thread Series Designator:  Unc single group   |
| Thread Size:  0.164 inches single group  Winding Operating Current:  3.0 amperes ac single component 4th secondary  Winding Operating Voltage:  6.30 ac volts single component all secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:                                       |
| Thread Size:  0.164 inches single group  Winding Operating Current:  3.0 amperes ac single component 4th secondary  Winding Operating Voltage:  6.30 ac volts single component all secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  12 standoff, solder lug              |
| Thread Size:  0.164 inches single group  Winding Operating Current:  3.0 amperes ac single component 4th secondary  Winding Operating Voltage:  6.30 ac volts single component all secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  12 standoff, solder lug  Shelf Life: |

No

Demilitarization:

## NSN 5950-00-552-9628

Power Transformer - Page 2 of 2



Fiig:

A058b0