## NSN 5950-00-553-3686

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-553-3686             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.062 inches single mounting facility single center group                 |
| Overall Height:   |
| 2.813 inches  |
| Frequency Rating:   |
| 380.0 hertz single component and 420.0 hertz single component             |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 1.938 inches  |
| Body Width:   |
| 1.812 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 2 secondary single component               |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Current:  |
| 1.95 amperes ac single component 1st secondary                            |
| Winding Operating Voltage:  |
| 6.40 ac volts single component 1st secondary                              |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 7 standoff, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

A058b0