NSN 5950-00-553-5548

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-553-5548

| view Online at https://aerobasegroup.com/nsn/5950-00-553-5548 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.625 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Frequency Rating: |
| 48.0 hertz single component and 62.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.875 inches |
| Body Width: |
| 3.062 inches |
| Body Height: |
| 3.562 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Operating Current: |
| 260.0 milliamperes ac single component 1st secondary |
| Winding Operating Voltage: |
| 90.00 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5950-00-553-5548

Power Transformer - Page 2 of 2

Fiig: A058b0

