

View Online at <https://aerobasegroup.com/nsn/5950-00-556-0611>

Reliability Indicator:

Not established

Inductance Rating:

1.00 millihenries single component single primary and 7.00 millihenries single component single primary and 12.50 millihenries single component single primary and 18.00 millihenries single component single primary and 30.00 millihenries single component single primary and 35.00 millihenries single component single primary and 39.00 millihenries single component single primary and 46.00 millihenries single component single primary and 59.00 millihenries single component single primary and 64.00 millihenries single component single primary and 71.00 millihenries single component single primary and 78.00 millihenries single component single primary and 83.00 millihenries single component single primary and 89.00 millihenries single component single primary and 96.00 millihenries single component single primary

Frequency Rating:

2.5 megahertz single component

Coil Form Type:

Solid single component

Body Length:

4.000 inches

Body Outside Diameter:

1.000 inches

Distance Between Mounting Facility Centers:

3.625 inches single mounting facility single center group

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single primary

Winding Function And Quantity:

1 primary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: