NSN 5950-00-556-1063

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-556-1063

Reliability Indicator:
Not established
Mounting Hole Diameter:
0.140 inches single group
Inductance Type:
Fixed
Inductance Rating:
1.50 henry single component single winding
Body Length:
1.406 inches
Body Width:
1.250 inches
Body Height:
1.312 inches
Distance Between Mounting Facility Centers:
0.906 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
Mounting Facility Quantity: 2 single group
2 single group
2 single group Mounting Method:
2 single group Mounting Method: Unthreaded hole single group
2 single group Mounting Method: Unthreaded hole single group Rating Method:
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current:
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding Terminal Type And Quantity:
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding Terminal Type And Quantity: 2 standoff insulator
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding Terminal Type And Quantity: 2 standoff insulator Shelf Life:
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding Terminal Type And Quantity: 2 standoff insulator Shelf Life: N/a
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding Terminal Type And Quantity: 2 standoff insulator Shelf Life: N/a
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding Terminal Type And Quantity: 2 standoff insulator Shelf Life: N/a Unit Of Measure:
2 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 80.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 300.000 single component single winding Terminal Type And Quantity: 2 standoff insulator Shelf Life: N/a Unit Of Measure: Demilitarization: