## NSN 5950-00-556-1626

Saturable Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-556-1626

Reliability Indicator:         Not established         Overall Length:         10.000 inches         Center To Center Distance Between Mounting Facilities Parallel To Length:         5.500 inches single mounting facility single center group         Center To Center Distance Between Mounting Facilities Parallel To Width:         4.000 inches         6.625 inches         Overall Height:         6.625 inches         Overall Width:         7.000 inches         Frequency Rating:         60.0 hertz single component         Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         6 single group         Mounting Method:         Threaded stud single group         Winding Function And Quantity:         1 primary and 1 control single component         Saturation Current Rating:         700.0 milliamperes         Thread Size:         0.250 inches single group         Dr Resistance Rating In Ohms:         3.000 single component single control         Winding Operating Voltage:         120.00 a volts single component single primary         Thread Series Designator:         100.0 single group
10.000 inchesCenter To Center Distance Between Mounting Facilities Parallel To Length:5.500 inches single mounting facility single center groupCenter To Center Distance Between Mounting Facilities Parallel To Width:4.000 inches single mounting facility single center groupOverall Height:6.625 inchesOverall Width:7.000 inchesFrequency Rating:60.0 hertz single componentHolmster Type:Hermetically sealedMounting Facility Quantity:6 single groupMounting Method:Threaded stud single groupVinding Function And Quantity:1 primary and 1 control single componentSaturation Current Rating:700.0 milliamperesThread Size:0.250 inches single groupDiread stud single group20.00 single component single controlWinding Control single controlChrees Single groupDiread Size:0.020 inches single groupDiread Size:0.000 single component single primary1 primary and 1 control single controlWinding Operating Voltage:1 2.000 ac volts single component single primary1 2.000 ac volts single groupContext Single groupContext Single component single primaryThread Series Designator:1 2.000 ac volts single component single primaryChread Series Designator:Conting GroupContext Single groupContext Single groupContext Single groupContext Single Group<
10.000 inchesCenter To Center Distance Between Mounting Facilities Parallel To Length:5.500 inches single mounting facility single center groupCenter To Center Distance Between Mounting Facilities Parallel To Width:4.000 inches single mounting facility single center groupOverall Height:6.625 inchesOverall Width:7.000 inchesFrequency Rating:60.0 hertz single componentHolmster Type:Hermetically sealedMounting Facility Quantity:6 single groupMounting Method:Threaded stud single groupVinding Function And Quantity:1 primary and 1 control single componentSaturation Current Rating:700.0 milliamperesThread Size:0.250 inches single groupDiread stud single group20.00 single component single controlWinding Control single controlChrees Single groupDiread Size:0.020 inches single groupDiread Size:0.000 single component single primary1 primary and 1 control single controlWinding Operating Voltage:1 2.000 ac volts single component single primary1 2.000 ac volts single groupContext Single groupContext Single component single primaryThread Series Designator:1 2.000 ac volts single component single primaryChread Series Designator:Conting GroupContext Single groupContext Single groupContext Single groupContext Single Group<
Center To Center Distance Between Mounting Facilities Parallel To Length:         5.500 inches single mounting facility single center group         Center To Center Distance Between Mounting Facilities Parallel To Width:         4.000 inches single mounting facility single center group         Overall Height:         6.625 inches         Overall Width:         7.000 inches         Frequency Rating:         60.0 hertz single component         Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         6 single group         Mounting Method:         Threaded stud single group         Winding Function And Quantity:         1 primary and 1 control single component         Saturation Current Rating:         700.0 milliamperes         Thread Size:         0.250 inches single group         Dc Resistance Rating In Ohms:         3.000 single component single control         Winding Operating Voltage:         120.00 ac volts single component single primary         Thread Series Designator:         120.00 ac volts single component single primary
<ul> <li>5.500 inches single mounting facility single center group</li> <li>Center To Center Distance Between Mounting Facilities Parallel To Width:</li> <li>4.000 inches single mounting facility single center group</li> <li>Overall Height:</li> <li>6.625 inches</li> <li>Overall Width:</li> <li>7.000 inches</li> <li>Frequency Rating:</li> <li>60.0 hertz single component</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>6 single group</li> <li>Mounting Method:</li> <li>Threaded stud single group</li> <li>Winding Function And Quantity:</li> <li>1 primary and 1 control single component</li> <li>Saturation Current Rating:</li> <li>700.0 milliamperes</li> <li>Thread Size:</li> <li>0.250 inches single group</li> <li>Dc Resistance Rating In Ohms:</li> <li>3.000 single component single primary</li> <li>Thread Series Designator:</li> <li>Unc single group</li> </ul>
Center To Center Distance Between Mounting Facilities Parallel To Width:4.000 inches single mounting facility single center groupOverall Height:6.625 inchesOverall Width:7.000 inchesFrequency Rating:60.0 hertz single componentInclosure Type:Hermetically sealedMounting Facility Quantity:6 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary and 1 control single componentSaturation Current Rating:700.0 milliamperesThread Size:0.250 inches single groupWinding Operating Nottage:1.2000 ac volts single component single primary120.00 ac volts single component single primary120.00 ac single groupWinding Operating Voltage:120.00 ac volts single component single primary120.00 a
4.000 inches single mounting facility single center group Overall Height: 6.625 inches Overall Width: 7.000 inches Frequency Rating: 60.0 hertz single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Mounting Operating Nottage: 3.000 single component single control Winding Operating Vottage: 120.00 ac volts single component single primary Thread Sizes Designator: Unc single group
Overall Height:6.625 inchesOverall Width:7.000 inchesFrequency Rating:60.0 hertz single componentInclosure Type:Hermetically sealedMounting Facility Quantity:6 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary and 1 control single componentSaturation Current Rating:700.0 milliamperesThread Size:0.250 inches single groupDc Resistance Rating In Ohms:3.000 single component single controlWinding Operating Voltage:120.00 ac volts single component single primaryThread Series Designator:Unc single group
6.625 inches Overall Width: 7.000 inches Frequency Rating: 60.0 hertz single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Overall Width:7.000 inchesFrequency Rating:60.0 hertz single componentInclosure Type:Hermetically sealedMounting Facility Quantity:6 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary and 1 control single componentSaturation Current Rating:700.0 milliamperesThread Size:0.250 inches single groupWinding Operating Voltage:120.00 ac volts single component single primaryThread Series Designator:Unc single group
<ul> <li>7.000 inches</li> <li>Frequency Rating:</li> <li>60.0 hertz single component</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>6 single group</li> <li>Mounting Method:</li> <li>Threaded stud single group</li> <li>Winding Function And Quantity:</li> <li>1 primary and 1 control single component</li> <li>Saturation Current Rating:</li> <li>700.0 milliamperes</li> <li>Thread Size:</li> <li>0.250 inches single group</li> <li>Dc Resistance Rating In Ohms:</li> <li>3.000 single component single control</li> <li>Winding Operating Voltage:</li> <li>120.00 ac volts single component single primary</li> <li>Itread Series Designator:</li> <li>Unc single group</li> </ul>
Frequency Rating:60.0 hertz single componentInclosure Type:Hermetically sealedMounting Facility Quantity:6 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary and 1 control single componentSaturation Current Rating:700.0 milliamperesThread Size:0.250 inches single groupDc Resistance Rating In Ohms:3.000 single component single controlWinding Operating Voltage:120.00 ac volts single component single primaryThread Series Designator:Unc single group
60.0 hertz single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Inclosure Type:Hermetically sealedMounting Facility Quantity:6 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary and 1 control single componentSaturation Current Rating:700.0 milliamperesThread Size:0.250 inches single groupDc Resistance Rating In Ohms:3.000 single component single controlWinding Operating Voltage:120.00 ac volts single component single primaryThread Series Designator:Unc single group
Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Mounting Facility Quantity: 6 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
6 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Threaded stud single group Winding Function And Quantity: 1 primary and 1 control single component Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
<ul> <li>Winding Function And Quantity:</li> <li>1 primary and 1 control single component</li> <li>Saturation Current Rating:</li> <li>700.0 milliamperes</li> <li>Thread Size:</li> <li>0.250 inches single group</li> <li>Dc Resistance Rating In Ohms:</li> <li>3.000 single component single control</li> <li>Winding Operating Voltage:</li> <li>120.00 ac volts single component single primary</li> <li>Thread Series Designator:</li> <li>Unc single group</li> </ul>
<ul> <li>1 primary and 1 control single component</li> <li>Saturation Current Rating:</li> <li>700.0 milliamperes</li> <li>Thread Size:</li> <li>0.250 inches single group</li> <li>Dc Resistance Rating In Ohms:</li> <li>3.000 single component single control</li> <li>Winding Operating Voltage:</li> <li>120.00 ac volts single component single primary</li> <li>Thread Series Designator:</li> <li>Unc single group</li> </ul>
Saturation Current Rating: 700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
700.0 milliamperes Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Thread Size: 0.250 inches single group Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
Dc Resistance Rating In Ohms: 3.000 single component single control Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
<ul> <li>3.000 single component single control</li> <li>Winding Operating Voltage:</li> <li>120.00 ac volts single component single primary</li> <li>Thread Series Designator:</li> <li>Unc single group</li> </ul>
Winding Operating Voltage: 120.00 ac volts single component single primary Thread Series Designator: Unc single group
120.00 ac volts single component single primary <b>Thread Series Designator:</b> Unc single group
Thread Series Designator: Unc single group
Unc single group
Terminal Type And Quantity:
9 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0