NSN 5950-00-556-1716

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-556-1716

Reliability Indicator:
Not established
Frequency Rating:
800.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core and brought out to terminal single component
Body Length:
1.375 inches
Body Width:
1.000 inches
Body Height:
1.000 inches
Distance Between Mounting Facility Centers:
0.750 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Operating Current:
2.0 milliamperes ac single component single secondary
Winding Operating Voltage:
50.00 ac volts single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5950-00-556-1716

Power Transformer - Page 2 of 2



Fiig:

A058b0