

View Online at <https://aerobasegroup.com/nsn/5950-00-556-6724>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.922 inches single mounting facility single center group and 1.954 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.672 inches single mounting facility single center group and 1.704 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.563 inches

Body Width:

2.250 inches

Body Height:

4.094 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

23.3 milliamperes ac single component single primary

Winding Power Rating:

3.92 volts-amperes single component single primary

Winding Operating Voltage:

56.00 ac volts single component single primary and 67.50 ac volts single component single primary and 81.00 ac volts single component single primary and 97.00 ac volts single component single primary and 116.50 ac volts single component single primary and 140.00 ac volts single component single primary and 168.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0