NSN 5950-00-556-9351

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-556-9351

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.312 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.686 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz single component and 70.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 4.312 inches |
| Body Width: |
| 3.688 inches |
| Body Height: |
| 4.500 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 6 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 14 standoff, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |