

View Online at <https://aerobasegroup.com/nsn/5950-00-557-5433>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Body Length:

Between 3.307 inches and 3.317 inches

Body Width:

Between 1.323 inches and 1.333 inches

Body Height:

Between 1.370 inches and 1.380 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

35.0 milliamperes ac single component single secondary

Winding Operating Voltage:

92.00 ac volts single component single secondary and 97.80 ac volts single component single secondary and 103.50 ac volts single component single secondary and 109.20 ac volts single component single secondary and 1.28 ac kilovolts single component single secondary

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0