## NSN 5950-00-557-5447

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-557-5447

| Reliability Indicator:  |
|---|
| Not established   |
|   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.281 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.125 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 1.625 inches  |
| Body Width:   |
| 1.500 inches  |
| Body Height:  |
| 1.656 inches  |
| Inclosure Type:   |
| Open  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 4 secondary single component               |
| Thread Size:  |
| 0.112 inches single group   |
| Winding Operating Current:  |
| 600.0 milliamperes ac single component 2nd secondary                      |
| Winding Operating Voltage:  |
| 6.30 ac volts single component all secondary                              |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 10 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
|   |

Fiig:

A058b0