

View Online at <https://aerobasegroup.com/nsn/5950-00-557-6779>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.625 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.125 inches

Body Width:

4.750 inches

Body Height:

5.875 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

6.7 amperes ac single component 4th secondary

Winding Operating Voltage:

240.00 ac volts single component 2nd secondary

Special Features:

1 primary winding; 7 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0