

View Online at <https://aerobasegroup.com/nsn/5950-00-563-5416>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.500 inches single mounting facility single center group

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

47.5 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

7.000 inches

Body Width:

5.750 inches

Body Height:

6.500 inches

Maximum Operating Temp:

50.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

8.6 amperes ac single component single secondary

Winding Power Rating:

1.0 kilovolt-amperes single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single secondary

Terminal Type And Quantity:

15 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0