NSN 5950-00-563-5416

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-563-5416

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 4.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.500 inches single mounting facility single center group **Mounting Slot Width:** 0.281 inches single group **Frequency Rating:** 47.5 hertz single component and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to core single component **Body Length:** 7.000 inches **Body Width:** 5.750 inches **Body Height:** 6.500 inches **Maximum Operating Temp:** 50.0 degrees celsius Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Flange single group and slot single group Winding Function And Quantity: 2 primary single component and 1 secondary single component Winding Operating Current: 8.6 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single secondary **Terminal Type And Quantity:** 15 screw Shelf Life: N/a Unit Of Measure: ---

NSN 5950-00-563-5416

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

