NSN 5950-00-566-1124

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-566-1124

| view Online at https://acrobasegroup.com/nsn/3330-00-300-1124 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.250 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.250 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.500 inches |
| Body Width: |
| 3.250 inches |
| Body Height: |
| 3.375 inches |
| End Application: |
| Compressor for arsr-3 (srse) |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 3.0 amperes ac single component single secondary |
| Winding Power Rating: |
| 75.0 volts-amperes single component single secondary |
| Winding Operating Voltage: |
| 25.00 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 5 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5950-00-566-1124

Power Transformer - Page 2 of 2



Fiig:

A058b0