

View Online at <https://aerobasegroup.com/nsn/5950-00-566-5401>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.990 inches single mounting facility single center group

Frequency Rating:

22.0 kilohertz single component and 26.0 kilohertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Body Length:

1.310 inches

Body Width:

0.820 inches

Body Height:

0.900 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

10.0 amperes ac single component single primary

Winding Operating Voltage:

8.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0