

View Online at <https://aerobasegroup.com/nsn/5950-00-566-5401>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.990 inches single mounting facility single center group

**Frequency Rating:**

22.0 kilohertz single component and 26.0 kilohertz single component

**Input-output Phase Relationship:**

Three phase to single phase single component

**Body Length:**

1.310 inches

**Body Width:**

0.820 inches

**Body Height:**

0.900 inches

**Maximum Operating Temp:**

170.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

10.0 amperes ac single component single primary

**Winding Operating Voltage:**

8.00 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0