

View Online at <https://aerobasegroup.com/nsn/5950-00-566-6768>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.000 inches

Body Width:

3.562 inches

Body Height:

4.688 inches

End Application:

Arsr-1, fa-7148 transmitter/modulator cabinet

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

24 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

2.43 amperes ac single component single secondary

Winding Operating Voltage:

40.00 ac volts single component single secondary

Special Features:

Secondary tapped at 36v, 38v, 40v, 42v and 44v; function, transformer, power, step-down; reference data, t-1101, instruction book, arsr-1d/e/f, vol 5, sec 10, pg 10-41

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0