## NSN 5950-00-568-1924

Reactor-transformer - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5950-00-568-1924

Delichility Indicator
Reliability Indicator:
Not established
Overall Length:
4.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.760 inches single mounting facility single center group
Overall Height:
3.620 inches
Overall Width:
4.000 inches
Frequency Rating:
400.0 hertz all components and 460.0 hertz all components
Input-output Phase Relationship:
Single phase to single phase single component
Primary To Secondary Turn Ratio:
1 to 7 2nd component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical 1st component single secondary
Thread Size:
0.190 inches single group
Winding Operating Current:
50.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
200.000 1st component single winding
Winding Operating Voltage:
6.30 ac volts 2nd component single secondary and 860.00 ac volts 2nd component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 tab, solder lug
Specification Or Standard:
Tf1rx07yy type
Shelf Life:

## NSN 5950-00-568-1924

Reactor-transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0