# NSN 5950-00-570-5606

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-570-5606

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.125 inches single mounting facility single center group

#### **Overall Height:**

6.750 inches

#### Frequency Rating:

320.0 hertz single component and 420.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

Between 5.094 inches and 5.219 inches

#### **Body Width:**

Between 3.937 inches and 4.062 inches

#### **Body Height:**

Between 5.781 inches and 5.969 inches

# **Maximum Operating Temp:**

65.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 4 secondary single component

# Thready Qty Per Inch (tpi):

20 single group

# **Thread Size:**

0.250 inches single group

#### **Winding Operating Current:**

8.0 milliamperes ac single component 2nd secondary

# **Winding Operating Voltage:**

900.00 ac volts single component 4th secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

14 wire hook

# NSN 5950-00-570-5606

Power Transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0