

View Online at <https://aerobasegroup.com/nsn/5950-00-570-9253>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

6.000 inches

Body Width:

4.875 inches

Body Height:

7.906 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

18 single group

Thread Size:

0.312 inches single group

Winding Operating Current:

6.0 amperes ac single component 4th secondary

Winding Operating Voltage:

5.10 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0