# NSN 5950-00-570-9310

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-570-9310

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

#### **Overall Height:**

3.812 inches

**Overall Width:** 

2.375 inches

Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to inclosure single component

**Body Length:** 

2.750 inches

#### Maximum Operating Temp:

85.0 degrees celsius

### Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

#### Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

#### Winding Operating Current:

10.0 amperes ac single component single secondary

#### Winding Operating Voltage:

2.60 ac volts single component single secondary

### **Thread Series Designator:**

Unf single group

#### **Terminal Type And Quantity:**

5 standoff, solder lug

Shelf Life:

N/a

# NSN 5950-00-570-9310

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

