NSN 5950-00-575-9640

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-575-9640 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.546 inches single mounting facility single center group |
| Overall Width: |
| 1.375 inches |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 1.125 inches |
| Body Width: |
| 0.875 inches |
| Body Height: |
| 0.875 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 40 single group |
| Thread Size: |
| 0.112 inches single group |
| Winding Operating Current: |
| 20.0 milliamperes dc single component single secondary |
| Winding Operating Voltage: |
| 12.60 ac volts single component single primary and 115.00 ac volts single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 5 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-575-9640

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0