

View Online at <https://aerobasegroup.com/nsn/5950-00-577-0664>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Mounting Slot Width:

0.250 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

500.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

6.125 inches

Body Width:

4.500 inches

Body Height:

5.375 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

4.4 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single secondary

Terminal Type And Quantity:

1 connector, receptacle and 1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0