NSN 5950-00-577-1177

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-577-1177

Facilities Parallel To Length:

Facilities Parallel To Width:

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilitie |
| 1.380 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilitie |
| 1.450 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 2.938 inches |
| Body Width: |
| 3.190 inches |
| Body Height: |
| 3.440 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange and slot single group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Winding Operating Current: |
| 10.0 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 6.60 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 9 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |