

View Online at <https://aerobasegroup.com/nsn/5950-00-577-9120>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.188 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

5.062 inches

Body Width:

4.312 inches

Body Height:

5.125 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

260.0 milliamperes ac single component single secondary

Winding Operating Voltage:

275.00 ac volts single component single secondary and 1.10 ac kilovolts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

1 tab, solder lug and 6 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0