

View Online at <https://aerobasegroup.com/nsn/5950-00-578-1055>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.625 inches single mounting facility single center group

Mounting Slot Width:

0.375 inches single group

Frequency Rating:

50.0 hertz single component and 1.5 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.875 inches

Body Width:

4.750 inches

Body Height:

4.750 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Winding Operating Current:

8.0 amperes ac single component 4th secondary

Winding Power Rating:

50.4 volts-amperes single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 4th secondary

Special Features:

1 primary winding; 5 secondary windings

Terminal Type And Quantity:

14 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0