# NSN 5950-00-578-1682

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-578-1682

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

# **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group

#### **Overall Height:**

5.280 inches

#### **Frequency Rating:**

54.0 hertz single component and 66.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to core single component

#### **Body Length:**

3.560 inches

#### **Body Width:**

3.060 inches

#### **Body Height:**

4.880 inches

# **Maximum Operating Temp:**

70.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

#### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# Thread Size:

0.164 inches single group

# **Winding Operating Current:**

10.0 amperes ac single component single secondary

# **Winding Operating Voltage:**

6.60 ac volts single component single secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

9 tab, solder lug

# NSN 5950-00-578-1682

Power Transformer - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0