

View Online at <https://aerobasegroup.com/nsn/5950-00-578-2749>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.187 inches single group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.375 inches

Body Width:

1.500 inches

Body Height:

1.930 inches

Distance Between Mounting Facility Centers:

2.000 inches single mounting facility single center group

End Application:

Wsd: landing craft air cushion (lcac); nimitz class cvn; los angeles ssn (688); kidd ddg; ticonderoga cg (47); forrestal cv; virginia cgn (41);
sturgeon ssn (637); spruance dd (963)

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

48.0 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

42.00 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0