

View Online at <https://aerobasegroup.com/nsn/5950-00-578-5698>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.688 inches single mounting facility single center group

Overall Height:

4.312 inches

Overall Width:

4.062 inches

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.500 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

8.2 amperes ac single component single secondary

Winding Operating Voltage:

396.00 ac volts single component single primary and 440.00 ac volts single component single primary and 484.00 ac volts single component single primary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0