NSN 5950-00-578-8245

Power Transformer - Page 1 of 2



Vi	iew Online at https://aerobasegroup.com/nsn/5950-00-578-8245
R	eliability Indicator:
Ν	ot established
C	enter To Center Distance Between Mounting Facilities Parallel To Length:
1.	906 inches single mounting facility single center group
C	enter To Center Distance Between Mounting Facilities Parallel To Width:
0.	750 inches single mounting facility single center group
F	requency Rating:
38	30.0 hertz single component and 420.0 hertz single component
In	put-output Phase Relationship:
TI	hree phase to three phase single component
W	/inding Shielding Method:
In	ternal shield brought out to terminal single component
В	ody Length:
2.	469 inches
В	ody Width:
1.	312 inches
В	ody Height:
3.	625 inches
In	closure Type:
Н	ermetically sealed
M	ounting Facility Quantity:
4	single group
M	ounting Method:
TI	hreaded stud single group
W	linding Function And Quantity:
1	primary single component and 1 secondary single component
TI	hready Qty Per Inch (tpi):
32	2 single group
TI	hread Size:
0.	138 inches single group
W	/inding Operating Voltage:
11	15.00 ac volts single component single secondary
TI	hread Series Designator:
U	nc single group
T	erminal Type And Quantity:
7	standoff, solder lug
S	helf Life:
N.	/a
U	nit Of Measure:
D	emilitarization:

No

NSN 5950-00-578-8245

Power Transformer - Page 2 of 2



Fiig:

A058b0