

View Online at <https://aerobasegroup.com/nsn/5950-00-578-8882>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.672 inches single mounting facility single center group and 1.702 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.422 inches single mounting facility single center group and 1.452 inches single mounting facility single center group

Impedance Rating In Ohms:

750.0 single component 1st secondary

Frequency Rating:

50.0 hertz single component and 20.0 kilohertz single component

Maximum Transformer Power Rating:

5.0 watts single component

Primary To Secondary Turn Ratio:

5-3/4 to 1 single component

Winding Shielding Method:

Grounded to inclosure, core and brought out to terminal single component

Body Length:

Between 1.187 inches and 1.312 inches

Body Width:

Between 1.937 inches and 2.062 inches

Body Height:

Between 3.000 inches and 3.125 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

20.0 milliamperes dc single component all primary

Test Data Document:

56232-1651983 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0