NSN 5950-00-581-2632

Pulse Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-581-2632

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.116 inches single group |
| Inductance Rating: |
| 600.00 millihenries single component single secondary |
| Primary To Secondary Turn Ratio: |
| 3-1/2 to 1 single component |
| Pulse Repetition Rate: |
| 310.0 hertz single component |
| Body Length: |
| 2.375 inches |
| Body Width: |
| 3.125 inches |
| Body Height: |
| 2.625 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 1.4 amperes ac single component single secondary |
| Dc Resistance Rating In Ohms: |
| 54.600 single component single secondary |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

. .

A058b0