

View Online at <https://aerobasegroup.com/nsn/5950-00-581-8672>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group

Frequency Rating:

320.0 hertz single component and 522.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.375 inches

Body Width:

3.312 inches

Body Height:

2.812 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

0.05 amperes ac single component 1st secondary

Winding Operating Voltage:

115.00 ac volts single component single primary and 200.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

21 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0