

View Online at <https://aerobasegroup.com/nsn/5950-00-581-9072>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

6.875 inches

Body Width:

5.500 inches

Body Height:

4.562 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

8 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

500.0 amperes ac single component single secondary

Winding Operating Voltage:

110.50 ac pounds per hour wet single component single primary

Special Features:

Case metal material; 4 additional mtg holes on 3.625 in. By 5.000 in. Mtg centers

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0