

View Online at <https://aerobasegroup.com/nsn/5950-00-581-9199>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.094 inches single mounting facility single center group and 3.141 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.890 inches single mounting facility single center group and 2.922 inches single mounting facility single center group

Mounting Slot Width:

0.213 inches single group and 0.223 inches single group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.000 inches

Body Width:

4.031 inches

Body Height:

4.500 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Winding Operating Current:

600.0 milliamperes ac single component 4th secondary

Winding Power Rating:

565.5 volts-amperes single component 3rd secondary

Winding Operating Voltage:

56.30 ac volts single component 1st secondary

Special Features:

One primary winding and six secondary windings

Test Data Document:

56232-631198 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

19 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0