

View Online at <https://aerobasegroup.com/nsn/5950-00-581-9199>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.094 inches single mounting facility single center group and 3.141 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.890 inches single mounting facility single center group and 2.922 inches single mounting facility single center group

**Mounting Slot Width:**

0.213 inches single group and 0.223 inches single group

**Frequency Rating:**

50.0 hertz single component and 1.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

5.000 inches

**Body Width:**

4.031 inches

**Body Height:**

4.500 inches

**Maximum Operating Temp:**

170.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Winding Operating Current:**

600.0 milliamperes ac single component 4th secondary

**Winding Power Rating:**

565.5 volts-amperes single component 3rd secondary

**Winding Operating Voltage:**

56.30 ac volts single component 1st secondary

**Special Features:**

One primary winding and six secondary windings

**Test Data Document:**

56232-631198 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

19 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0