NSN 5950-00-583-0589

Reactor - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-00-583-0589

| Not established |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.125 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 8.00 henry single component single winding |
| Body Length: |
| 2.688 inches |
| Body Width: |
| 2.688 inches |
| Body Height: |
| 2.406 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 105.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 160.000 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5950-00-583-0589

Reactor - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A058b0