NSN 5950-00-583-0888

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-583-0888

Reliability Indicator:
Not established
Center To Center Dis

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.438 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.875 inches

Body Width:

3.438 inches

Body Height:

6.625 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

180.0 milliamperes ac single component single secondary

Winding Operating Voltage:

3.00 ac kilovolts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-583-0888

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0