NSN 5950-00-583-0909

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-583-0909

| View Online at https://aerobasegroup.com/nsn/5950-00-583-0909 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.500 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.430 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.223 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.370 inches |
| Body Width: |
| 2.680 inches |
| Body Height: |
| 2.900 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary, fixed autotransformer type single component |
| Winding Operating Current: |
| 423.7 milliamperes ac single component single primary input |
| Winding Power Rating: |
| 50.0 volts-amperes single component single primary input |
| Winding Operating Voltage: |
| 28.00 ac volts single component single primary output and 114.00 ac volts single component single primary output |
| Terminal Type And Quantity: |
| 4 standoff, threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0