## NSN 5950-00-583-4206

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-583-4206

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 5.875 inches single mounting facility single center group   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.000 inches single mounting facility single center group   |
| Frequency Rating:   |
| 50.0 hertz single component or 60.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Maximum Transformer Power Rating:   |
| 600.0 watts single component  |
| Body Length:  |
| 7.375 inches  |
| Body Width:   |
| 3.375 inches  |
| Body Height:  |
| 4.625 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Slot single group   |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component   |
| Winding Operating Voltage:  |
| 110.00 ac pounds per hour dry single component single secondary and 120.00 ac pounds per hour with retaining chain single component |
| single secondary  |
| Terminal Type And Quantity:   |
| 1 line cord and 1 connector, receptacle   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |