

View Online at <https://aerobasegroup.com/nsn/5950-00-583-4243>

**Reliability Indicator:**

Not established

**Transformer Function:**

Input

**Impedance Rating In Ohms:**

5000.0 single component single secondary

**Frequency Rating:**

60.0 hertz single component and 15.0 kilohertz single component

**Maximum Transformer Power Rating:**

10.0 decibels single component

**Primary To Secondary Turn Ratio:**

1 to 1 single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core and brought out to terminal single component

**Body Length:**

Between 0.735 inches and 0.797 inches

**Body Width:**

Between 0.735 inches and 0.797 inches

**Body Height:**

Between 1.031 inches and 1.156 inches

**Distance Between Mounting Facility Centers:**

0.844 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

40 single group

**Thread Size:**

0.112 inches single group

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0