

View Online at <https://aerobasegroup.com/nsn/5950-00-583-4243>

Reliability Indicator:

Not established

Transformer Function:

Input

Impedance Rating In Ohms:

5000.0 single component single secondary

Frequency Rating:

60.0 hertz single component and 15.0 kilohertz single component

Maximum Transformer Power Rating:

10.0 decibels single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

Between 0.735 inches and 0.797 inches

Body Width:

Between 0.735 inches and 0.797 inches

Body Height:

Between 1.031 inches and 1.156 inches

Distance Between Mounting Facility Centers:

0.844 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0