

View Online at <https://aerobasegroup.com/nsn/5950-00-583-4980>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 4.531 inches and 4.593 inches

Body Width:

Between 4.094 inches and 4.156 inches

Body Height:

Between 5.407 inches and 5.469 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

95.00 ac volts single component single primary and 105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 190.00 ac volts single component single primary and 210.00 ac volts single component single primary and 230.00 ac volts single component single primary and 250.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

21 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0